

# **3" IronFlex Horseshoe Bollard Kit**

**PROTECTIVE GUARDING - SLOWSTOP®** 

SPEC SHEET | P/N SS3Y-36-HS-36

## **Product Specifications**

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal				
Diameter	3" (2.5" ANSI Schedule 40)				
Dimensions	36" H x 36" W				
Product Weight	97 lb.				
Impact Rating	I9-5 Rail (10,200 joules), I15-3 Post (3,100 joules)				
Temperature Rating	-40°F - 150°F				
Pipe Coating	60 µm Galvanized + 150 µm Polyester Outdoor Powder Coating				
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating				
Set Screws	M12				
Anchor Screws	Eight (8) 5/8" x 4" Concrete				

### **Recommended Uses**

Pedestrian protection	
Rack and equipment guarding	
Access denial	
Pre- and post-tensioned concrete	

**Post Impact Chart** 

#### **Rail Impact Chart**

Impact Angle	90°	45°	30°	Impact Angle	90°	45°	30°
Rating (joules)	10,200	20,406	40,800	Rating (joules)	6,100	12,204	24,400
ANSI MH 31.2	19-5	calculated	calculated	ANSI MH 31.2	l15-3	calculated	calculated
Mass (Ibs)	Speed (mph)	Speed (mph)	Speed (mph)	Mass (lbs)	Speed (mph)	Speed (mph)	Speed (mph)
1,000	15.0	21.2	30.0	1,000	11.6	16.4	23.2
2,000	10.6	15.0	21.2	2,000	8.2	11.6	16.4
4,000	7.5	10.6	15.0	4,000	5.8	8.2	11.6
5,000	6.7	9.5	13.4	5,000	5.2	7.3	10.4
6,000	6.1	8.7	12.2	6,000	4.7	6.7	9.5
8,000	5.3	7.5	10.6	8,000	4.1	5.8	8.2
10,000	4.7	6.7	9.5	10,000	3.7	5.2	7.3
12,500	4.2	6.0	8.5	12,500	3.3	4.6	6.6
15,000	3.9	5.5	7.7	15,000	3.0	4.2	6.0

4955 Stout Drive, San Antonio, TX 78219

(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com

#### impactrecovery.com

January 2024

©2024 Impact Recovery Systems, Inc.\* All rights reserved. Impact Recovery Systems, OneBase, and Tuff Curb are registered trademarks of Impact Recovery Systems, Inc.\* SlowStop® is a registered trademark of SlowStop Guarding Systems, LLC.®

The products mentioned in this document are covered by the following U.S. and international patent numbers: 7,195,422 | 7,621,691 | D937,700 | D620,823 | EP 2 267 225 | EP 2 888 412 | 9,938,677 | 11,136,735 | D932,875. Other U.S. and International patents pending.

