



# 4" IronFlex Rack End Guard

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS4Y-REP-XX**



## Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	4" (3.5" Schedule 40 Steel)
Dimensions	7 ¼" H to Centerline (9 ¼" Overall)
Max Tilt	4"
Impact Rating	I9-7 (20,000 joules)
Temperature Rating	-40°F - 150°F
Pipe Coating	60 µm Galvanized + 150 µm Polyester Outdoor Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Powder Coating
Set Screws	M16
Anchor Screws	Eight (8) 5/8" x 5-1/2" Concrete
Widths	Custom up to 126" (some widths may use 3 pedestals)

## Recommended Uses

- Heavy forklift traffic
- Pallet and storage rack ends
- Pallet stops
- Electric panel protection
- Wall guards
- Loading dock bays

## Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	20,000	40,012	80,000
ANSI MH 31.2	I9-7	calculated	calculated
Mass (lbs)	Speed (mph)	Speed (mph)	Speed (mph)
5,000	9.4	13.3	18.8
7,500	7.7	10.8	15.3
10,000	6.6	9.4	13.3
12,500	5.9	8.4	11.9
15,000	5.4	7.7	10.8
17,500	5.0	7.1	10.0
20,000	4.7	6.6	9.4
25,000	4.2	5.9	8.4
30,000	3.8	5.4	7.7

4955 Stout Drive, San Antonio, TX 78219  
 (210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com  
 impactrecovery.com  
 January 2024

