




4" Rebounding Bollard Sign Post

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N SS4Y-42-SP, SS4Y-42-SP, SS4Y-42-HC, SS4Y-42-VA



Product Specifications

Sign Options	Reserved Handicap, Van Accessible
Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	4" (3.5" ANSI Schedule 40)
Bollard Height	42" overall
Sign Height	60" Above ground (ADA) to sign bottom (78" Overall) 102" Tall option
Product Weight	68 lb.
Impact Rating	I9-5 (10,200 joules)
Temperature Rating	-40°F - 150°F
Pipe Coating	60 µm Galvanized +150 µm Polyester Outdoor Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Reflective Sheeting	Engineer Grade Reflective Sheeting Substrate
Post Material	Aluminum Post, white
Set Screws	Five (5) M16
Anchor Screws	Four (4) 5/8" x 5-1/2" Concrete
Cap	Metal, RAL 1023 Yellow

Recommended Uses

Parking lot handicap parking spots
Reserved parking spaces
Sign face can be added for a variety of uses
Can be used on pre- and post-tensioned concrete
For use without costly wheel stops

Impact Chart

Impact Angle	90°
Rating	10,200 joules
ANSI MH 31.2	I9-5
Mass (lbs)	Speed (mph)
5,000	6.7
7,500	5.5
10,000	4.7
12,500	4.2
15,000	3.9
17,500	3.6
20,000	3.4
25,000	3.0
30,000	2.7

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com

January 2024

