




4" Rebounding Steel Bollard

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS4Y-42**



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	4.00" (3.5 ANSI Schedule 40)
Product Weight	62 lb.
Product Height	42" overall
Impact Rating	I9-5 (10,200 joules)
Temperature Rating	-40°F - 150°F
Pipe Coating	60 µm Galvanized + 150 µm Polyester Outdoor Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Set Screws	Five (5) M16
Anchor Screws	Four (4) 5/8" x 5-1/2" Concrete
Cap	Metal, RAL 1023 Yellow

Recommended Uses

Medium duty
Where forks or cantilevers typically shear bolts
Equipment and storage rack guarding
Pedestrian safety
Access denial
Pre- and post-tensioned concrete capable
Not for K-Rated security use

Impact Chart

Impact Angle	90°
Rating	10,200 joules
ANSI MH 31.2	I9-5
Mass (lbs)	Speed (mph)
5,000	6.7
7,500	5.5
10,000	4.7
12,500	4.2
15,000	3.9
17,500	3.6
20,000	3.4
25,000	3.0
30,000	2.7

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com

impactrecovery.com

January 2024



©2024 Impact Recovery Systems, Inc.® All rights reserved. Impact Recovery Systems, OneBase, and Tuff Curb are registered trademarks of Impact Recovery Systems, Inc.® SlowStop® is a registered trademark of SlowStop Guarding Systems, LLC.®

The products mentioned in this document are covered by the following U.S. and international patent numbers: 7,195,422 | 7,621,691 | D937,700 | D620,823 | D620,824 | D620,825 | EP 2 267 225 | EP 2 888 412 | 9,938,677 | 11,136,735 | D932,875. Other U.S. and International patents pending.