



5" Rebounding Bollard Sign Post

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET

P/N **SS5Y-42-SF-SP**, **SS5Y-42-SF-HC**, **SS5Y-42-SF-VA**



Product Specifications

Sign Options	Reserved Handicap, Van Accessible
Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	5.53" (5" ANSI Schedule 40)
Bollard Height	78" overall
Sign Height	60" Above ground (ADA) to sign bottom (78" Overall) 102" tall option
Product Weight	110 lb.
Impact Rating	ASTM F3016 - S10 - 5,000 pounds @ 10.4 mph
Temperature Rating	-40°F - 150°F
Pipe Coating	60 µm Galvanized +150 µm Polyester Outdoor Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Reflective Sheeting	Engineer Grade Reflective Sheeting Substrate
Post Material	Aluminum Post, white
Set Screws	Six (6) M16
Anchor Screws	Six (6) 3/4" x 5-1/2" Concrete
Cap	Metal, RAL 1023 Yellow

Recommended Uses

- Parking lot handicap parking spots
- Reserved parking spaces
- Sign face can be added for a variety of uses
- Can be used on pre- and post-tensioned concrete
- For use without costly wheel stops
- Avoid trip hazards in pedestrian travel lanes

4955 Stout Drive, San Antonio, TX 78219
 (210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com

January 2024

