




IronFlex Column Protectors Type 1

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N SS-T1Y-XX-CP



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Temperature Rating	-40°C - 70°C
Pipe Coating	EN-ISO 1461 Galvanized + Polyester Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Cap	Black Plastic
Impact Rating	24,000 joules/116kN
Anchors	(16) M16x140 concrete

Recommended Uses

Protects from impact to building structures
Guard columns and other vertical members

Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	24,400	48,815 calculated	97,600 calculated
Mass (kg)	Speed (kph)	Speed (kph)	Speed (kph)
3,000	14.5	20.5	29.0
4,000	12.6	17.8	25.1
5,000	11.2	15.9	22.5
6,000	10.3	14.5	20.5
7,000	9.5	13.4	19.0
8,000	8.9	12.6	17.8
9,000	8.4	11.9	16.8
10,000	8.0	11.2	15.9
15,000	6.5	9.2	13.0

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com
January 2024

