



IronFlex Rack End Guard Type 2

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N SS-T2Y-REP-XXX



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	101,6 mm x 6,3 mm pipe
Height	18,5 cm to centerline (24 cm overall)
Max Tilt	75 mm
Impact Rating	20.000 joules
Temperature Rating	-40°C - 70°C
Pipe Coating	Galvanized + Polyester Powder Coating
Base Coating	Environmentally Friendly Water-based E-Coat + Polyester Powder Coating
Widths	800 mm Part # SS-T2Y-REP-80 900 mm Part# SS-T2Y-REP-90 1100 mm Part# SS-T2Y-REP-100 1700 mm Part# SS-T2Y-REP-170 1900mm Part# SS-T2Y-REP-190

Recommended Uses

- Medium to heavy duty forklift traffic
- Pallet and storage rack ends
- Pallet stops
- Electric panel protection
- Wall guards
- Loading dock bays
- Conveyor loading/unloading

Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	20.000	40.012 calculated	80.000 calculated
Mass (kg)	Speed (kph)	Speed (kph)	Speed (kph)
3,000	13.1	18.6	26.3
4,000	11.4	16.1	22.8
5,000	10.2	14.4	20.4
6,000	9.3	13.1	18.6
7,000	8.6	12.2	17.2
8,000	8.0	11.4	16.1
9,000	7.6	10.7	15.2
10,000	7.2	10.2	14.4
15,000	5.9	8.3	11.8

4955 Stout Drive, San Antonio, TX 78219
 (210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
 impactrecovery.com
 January 2024

