



# Rebounding Steel Bollard Type 3

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS-T3Y-100**



## Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	177,8 mm (6,3 mm wall)
Height	100 cm
Impact Rating	26.700 joules, 265,4 kN
Temperature Rating	-40°C - 70°C
Pipe Coating	EN-ISO 1461 Galvanized + Polyester Powder Coating
Base Coating	Environmentally Friendly Water-based KTL Coating + Polyester Powder Coat C51 corrosion resistance
Set Screws	8 M16 x 2,00, 8 mm Hex
Anchor Screws	Eight (8) M16x140 Concrete
Cap	Black Plastic

## Recommended Uses

- Heavy duty guarding
- Door and wall protection
- Parking facilities
- Utility protection
- Pedestrian safety
- Access denial fuel pump protection
- Not for hostile vehicle security

## Impact Chart

Impact Angle	90°
Rating	26.700 joules
<b>Mass (kg)</b>	<b>Speed (kph)</b>
5,000	11.8
7,500	9.6
10,000	8.3
15,000	6.8
20,000	5.9
25,000	5.3
30,000	4.8
35,000	4.4
40,000	4.2

4955 Stout Drive, San Antonio, TX 78219  
 (210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com  
 impactrecovery.com  
 November 2024

