



4" IronFlex Column Protectors

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N SS4Y-24-CP



Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	4" Posts
Dimensions	Designed for column
Impact Rating	I15-7 (33,300 joules)
Temperature Rating	-40°F - 150°F
Pipe Coating	60 µm Galvanized + 150 µm Polyester Outdoor Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Set Screws	M16
Anchor Screws	16 5/8" x 5-1/2"

Recommended Uses

- Guards structural columns in moderately heavy traffic environments.
- Protects against impacts from pallet jacks, hand trucks, and forklifts.
- Suitable for warehouses, light manufacturing plants, and storage areas.
- Reduces facility repair costs from incidental collisions.
- Improves visibility of support columns in busy work zones.

Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	33,300	66,620	133,200
ANSI MH 31.2	I15-7	calculated	calculated
Mass (lbs)	Speed (mph)	Speed (mph)	Speed (mph)
5,000	12.1	17.1	24.2
10,000	8.6	12.1	17.1
15,000	7.0	9.9	14.0
20,000	6.1	8.6	12.1
30,000	4.9	7.0	9.9

4955 Stout Drive, San Antonio, TX 78219
 (210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com

October 2025

