



# 6" Rebounding Steel Bollard

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS6Y-42-RB**



### Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Diameter	6.63" (6" ANSI Schedule 40)
Product Weight	161 lb.
Product Height	42" overall
Impact Rating	I12-7 (26,700 joules)
Temperature Rating	-40°F - 150°F
Pipe Coating	60 µm Galvanized + 150 µm Polyester Outdoor Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Set Screws	Eight (8) M16
Anchor Screws	Eight (8) 3/4" x 5-1/2" Concrete
Cap	Metal, RAL 1023 Yellow

### Recommended Uses

Heavy duty
Primary exterior use
Exterior loading docks and warehouse ramps
Property entrances
Guard shacks
Exterior light poles
Propane cages, generators & fire hydrants
Equipment
Access denial
Pre- and post-tensioned concrete capable
Not for K-Rated security use

### Impact Chart

Impact Angle	90°
Rating	26,700 joules
ANSI MH 31.2	I12-7
Mass (lbs)	Speed (mph)
5,000	10.8
10,000	7.7
15,000	6.3
20,000	5.4
25,000	4.8
30,000	4.4
40,000	3.8
60,000	3.1
80,000	2.7

4955 Stout Drive, San Antonio, TX 78219  
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com  
impactrecovery.com

March 2026

