IronFlex 3-Sided Column Protectors Type 2

PROTECTIVE GUARDING - SLOWSTOP®

SPEC SHEET | P/N **SS-T2Y-XX-CP3-XX**

Product Specifications

Color	RAL 1023 Yellow Pipe on RAL 9005 Black Pedestal
Impact Rating	Rail 20,000 joules Post 10,200 joules
Temperature Rating	-40°C - 70°C
Pipe Coating	EN-ISO 1461 Galvanized + Polyester Powder Coating
Cast-Iron Coating	Environmentally Friendly Water-based E-Coat + Polyester Outdoor Powder Coating
Anchors	Eight (8) M16 x 140 concrete

Recommended Uses

Protects from impact to building structures

Guard columns and other vertical members

Rail Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	20,000	40,012 calculated	80,000 calculated
Mass (kg)	Speed (kph)	Speed (kph)	Speed (kph)
3.000	13,1	18,6	26,3
4.000	11,4	16,1	22,8
5.000	10,2	14,4	20,4
6.000	9,3	13,1	18,6
7.000	8,6	12,2	17,2
8.000	8,0	11,4	16,1
9.000	7,6	10,7	15,2
10.000	7,2	10,2	14,4
15.000	5,9	8,3	11,8

Post Impact Chart

Impact Angle	90°	45°	30°
Rating (joules)	10,200	20,406 calculated	40,800 calculated
Mass (kg)	Speed (kph)	Speed (kph)	Speed (kph)
3.000	9,4	13,3	18,8
4.000	8,1	11,5	16,3
5.000	7,3	10,3	14,5
6.000	6,6	9,4	13,3
7.000	6,1	8,7	12,3
8.000	5,7	8,1	11,5
9.000	5,4	7,7	10,8
10.000	5,1	7,3	10,3
15.000	4,2	5,9	8,4

4955 Stout Drive, San Antonio, TX 78219
(210) 736-4477 | 1-800-736-5256 | info@impactrecovery.com
impactrecovery.com

June 2026

©2026 Impact Recovery Systems, Inc.® All rights reserved. Impact Recovery Systems, OneBase, and Tuff Curb are registered trademarks of Impact Recovery Systems, Inc.® SlowStop® is a registered trademark of SlowStop Guarding Systems, LLC.®
The products mentioned in this document are covered by the following U.S. and international patent numbers: 7,195,422 | 7,621,691| D937,700 | D620,823 | D620,824 |D620,825 | EP 2 267 225 | EP 2 888 412 | 9,938,677 | 11,136,735 | D932,875. Other U.S. and International patents pending.